

MIRA-FOUNT

DURABLE AND RESISTANT

Insulated drinking trough

BMR GROUP

1501 Ampère street, suite 200
Boucherville (Québec) J4B 5Z5
450 655-6700
1 800 361-0885
bmr.co
agrizone.co

Features

Material	047-3385 Polyethylene	047-3455 Polyethylene
Type	One opening of 8 ¾ in (22 cm)	Two openings of 9 ¼ in (23 cm)
Ball closure	One 9 in (22,8 cm) ball closure	Two 10 in (25 cm) ball closures
Insulation	Urethane foam	Urethane foam
Dimensions	21 H x 26 P x 28 L in 53 H x 66 P x 71 L cm	25 ½ H x 24 P x 36 L in 65 H x 61 P x 91 L cm
Drinking height	14 in (35 cm)	18 in (45 cm)
Capacity	57 L (15 gal)	76 L (20 gal)
Minimum head required	25 dairy cows or 50 beefs	40 dairy cows or 100 beefs
Warranty	5 years	5 years
Material	047-3446 Polyethylene	
Type	One opening of 10 in (25 cm)	
Ball closure	One 10 ¾ in (27 cm) ball closure	
Insulation	Urethane foam	
Dimensions	26 ½ H x 31 P x 29 L in 67 x 79 x 73 cm	
Drinking height	18 in (45 cm)	
Capacity	112 L (30 gal)	
Minimum head required	30 dairy cows or 50 beefs	
Warranty	5 years	

Advantages

- No sharp edges
- Tough, high-impact resistant material
- Durability to stand up to livestock abuse
- Resistance to corrosion
- Extra insulation above the valve area
- Removable dome for quick and easy access to valve area
- 2 to 3 in (5 to 8 cm) urethane insulation
- Sealed and sloped bottom for easier cleaning




047-3455



047-3446



047-3385



Parts



Insulated
heat tube
047-3835